


MaxiForce™ Removable Bollard


Round HD Body, Padlock Operated, Round Style 2 Head, Heavy Duty Hinge Top Base (5")

Engineered installation details available to meet many performance standards (IBC, FBC, AASHTO).



Only 8" of lifting required to remove the bollard.

Flush surface when bollard is removed. Leaves no tripping hazard and won't catch snowplows or other maintenance equipment.



- No Maintenance / Durable steel construction
- One year warranty / Protected by \$1,000,000 in liability insurance
- No complex assembly required in the field
- Custom sizes, options, colors and finishes available upon request
- Finish options available (add code to the end of the model number)
 - Powder coated (PC)
 - Powder coated with DRYZINC primer (PCZ)
 - Hot dip galvanized (G)
 - Hot dip galvanized & powder coated (GPC)
- Reflective tape available upon request

Bollard Assy. Weight	Base Weight
54 lbs	60 lbs
Drawing Rev.	Created
1	11/2/2009

PROPRIETARY AND CONFIDENTIAL

THIS DRAWING CONTAINS PROPRIETARY INFORMATION OF BLUE EMBER TECHNOLOGIES, LLC. ANY USE OF THIS DRAWING OR THE INFORMATION CONTAINED HEREIN FOR OTHER THAN THE PURPOSE FOR WHICH THIS DRAWING IS FURNISHED IS FORBIDDEN.

	MaxiForce™ Traffic Control Bollards		
	7560 Main Street Sykesville, MD 21784 410-552-9888 (phone) - 410-552-9939 (fax) www.maxiforcebollards.com - sales@maxiforcebollards.com		
Model	MRHP-RS2-HDH5		
Size	File Name	MRHP-RS2-HDH5	
C	Scale	NA	DO NOT SCALE DRAWING
		Sheet	1 Of 1