




MaxiForce Removable Bollard


Round HD Body, Padlock Operated, Round Style 4 Head, Heavy Duty Hinge Top Base (4")

Engineered installation details available to meet many performance standards (IBC, FBC, AASHTO).



Only 8" of lifting required to remove the bollard.


Flush surface when bollard is removed. Leaves no tripping hazard and won't catch snowplows or other maintenance equipment.



- No Maintenance / Durable steel construction
- One year warranty / Protected by \$1,000,000 in liability insurance
- No complex assembly required in the field
- Custom sizes, options, colors and finishes available upon request
- Finish options available (add code to the end of the model number)
 - Powder coated (PC)
 - Powder coated with DRYZINC primer (PCZ)
 - Hot dip galvanized (G)
 - Hot dip galvanized & powder coated (GPC)
- Reflective tape available upon request

Bollard Assy. Weight	41 lbs
Base Weight	44 lbs
Drawing Rev.	Created 2/1/2021
PROPRIETARY AND CONFIDENTIAL	
THIS DRAWING CONTAINS PROPRIETARY INFORMATION OF BLUE EMBER TECHNOLOGIES, LLC. ANY USE OF THIS DRAWING OR THE INFORMATION CONTAINED HEREIN FOR OTHER THAN THE PURPOSE FOR WHICH THIS DRAWING IS FURNISHED IS FORBIDDEN.	

MaxiForce
7560 Main Street
Sykesville, MD 21784
tel: +1 (410) 552 9888
sales@maxiforcebollards.com
www.maxiforcebollards.com


MRHP-RS4-HDH4

C	DO NOT SCALE DRAWING	SHEET 1 OF 1
---	----------------------	--------------